

type number	(mm)	length (mm)	weight (kg/m)	strength class	max. tensile load (kN)	🔥
ZT 6_ZNCR	M6	2000	0,17	4.8	2,56	🔥🔥
ZT 8_ZNCR	M8	2000	0,31	4.8	4,69	🔥🔥
ZT 8_ZNC1	M8	1000	0,31	4.8	4,69	🔥🔥
ZT 8_ZNC3	M8	3000	0,31	4.8	4,69	🔥🔥
ZT 10_ZNCR	M10	2000	0,46	4.8	7,47	🔥🔥
ZT 10_ZNC3	M10	3000	0,46	4.8	7,47	🔥🔥
ZT 10_GMT	M10	1000	0,46	8.8	19,92	🔥🔥
ZT 12_ZNCR	M12	2000	0,70	4.8	10,89	🔥🔥



product description: The threaded rod is used to suspend the cable route under the ceiling or as part of the anchorage for fixing structures or their parts to the underlying material.

The stated maximum load applies to the load at rest.

DIN 975/976

surface finish: ZNC... / ZNCR - bichromatic galvanised
 GMT - non electrolytic plating, aluminum-zinc-layer 5-15 µm (equivalent Hot Dip Galvanized)

klasifikace 🔥: ČSN 73 0895 P 90-R
 DIN 4102-12 E 90
 STN 92 0205 PS 90
 Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.
 🔥 products are approved for standard constructions
 🔥 products are approved for non-standard constructions

storage: ČSN EN 60721-3-1