



**product description:**

box designated for distribution systems with voltage up to 500 V  
 for installation in insulated building facades 80-140 mm thick, or as a box under plaster  
 use as a distribution box, for measuring the lightning conductor terminal and other applications as required by the customer  
 box depth is adjustable  
 the set includes a box, flat lid V 180, seal and stainless-steel screws  
 it is recommended to use the enclosed seal to achieve IP44 protection  
 robust design  
 protected by European industrial design  
 installation video at [www.kopos.cz](http://www.kopos.cz)

material: PC ABS, halogen-free  
 color: box - gray, lid - white  
 self-snuffing: yes, within 30 s  
 temperature resistance: -25 - +60 °C  
 flaming loop test: 850 °C  
 fire class for underlying material: A1-F  
 protection types: IP30  
 protection types: IP44 - seal under the cover, plaster roughness up to 2 mm  
 weight: 475 g  
 meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21  
 storage: ČSN 64 0090





KUZ-V\_KB - individual boxes packed in separate carton

accessories: terminal plate S-KSK 2  
 screwless terminal plates TYP015, TYP016, TYP017, TYP018  
 support trunking TS35

recycling codes:



**Warning:** Incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person.  
 Inappropriate location - when using sealing, the box has IP44 protection, it must not be installed in an environment with higher protection requirements.  
 Product damage - if the box is visibly damaged, stop using it.  
 Follow the manufacturer's installation instructions according to the installation instructions, videos.  
 Under normal and foreseeable conditions of use, the installed box does not pose any risks to consumers.